

Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200. Standard must be consulted for specific requirements. **U.S. Department of Labor**

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved

OMB No. 1218-0072

IDENTITY (as Used on Label and List)

Unusual Fire and Explosion Hazards

PVC Plastic Conduit and fittings

Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

Onether I				
Section I Manufacturer's name	Emergency Telephor	a Numbar		
		Emergency Telephone Number		
Cor-Tek Conduit Solutions	(800)424-9300 (Chemtrec)		
By Rocky Mountain Colby Pipe				
Address (Number, Street, City, State and ZIP Code)	Telephone Number fo	or Information		
4950 McKennon RD.	541-276-0741			
	Date Prepared			
Pendleton Oregon 97801	05/03/2018			
	Signature of Prepare	(optional)		
Section II—Hazardous Ingredients/Identity Information				
Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL A	CGIH TLV	Other Limit Recommend	
Nontoxic/ nonhazardous solid				
Section III—Physical/Chemical Characteristics				
Section III—Physical/Chemical Characteristics Boiling Point N/A	Specific Gravity (H ₂ 0	= 1)		.95-1.5
Boiling Point N/A	Specific Gravity (H ₂ 0 Melting Point	= 1)		.95-1.5 390° F
Boiling Point N/A				
Boiling Point N/A Vapor Pressure (mm Hg) N/A Vapor Density (AIR = 1) N/A	Melting Point			390° F
Boiling Point Vapor Pressure (mm Hg) Vapor Density (AIR = 1) Solubility in Water N/A	Melting Point			390° F
Boiling Point Vapor Pressure (mm Hg) Vapor Density (AIR = 1) Solubility in Water N/A Appearance and Odor Grey plastic conduit	Melting Point			390° F
Boiling Point Vapor Pressure (mm Hg) Vapor Density (AIR = 1) Solubility in Water Appearance and Odor Grey plastic conduit Section IV—Fire and Explosion Hazard Data	Melting Point			390° F
N/A	Melting Point Evaporation Rate (Bu	ityl Acetate = 1)		390° F Solid
Boiling Point Vapor Pressure (mm Hg) Vapor Density (AIR = 1) Solubility in Water Appearance and Odor Grey plastic conduit Section IV—Fire and Explosion Hazard Data Flash Point (Method Used)	Melting Point Evaporation Rate (Bu	ityl Acetate = 1)		390° F Solid
Boiling Point Vapor Pressure (mm Hg) Vapor Density (AIR = 1) Solubility in Water Appearance and Odor Grey plastic conduit Section IV—Fire and Explosion Hazard Data Flash Point (Method Used) Flash Ignition Temp (ASTM D 1929) 735° F Extinguishing Media	Melting Point Evaporation Rate (Bu	ityl Acetate = 1)		390° F Solid
Boiling Point Vapor Pressure (mm Hg) Vapor Density (AIR = 1) Solubility in Water Appearance and Odor Grey plastic conduit Section IV—Fire and Explosion Hazard Data Flash Point (Method Used) Flash Ignition Temp (ASTM D 1929) 735° F	Melting Point Evaporation Rate (Bu	ityl Acetate = 1)		390° F Solid
Boiling Point Vapor Pressure (mm Hg) Vapor Density (AIR = 1) Solubility in Water N/A Appearance and Odor Grey plastic conduit Section IV—Fire and Explosion Hazard Data Flash Point (Method Used) Flash Ignition Temp (ASTM D 1929) 735° F Extinguishing Media Water spray, Foam CO 2, Dry chemical	Melting Point Evaporation Rate (Bu	LEL N/A	N	390° F Solid

Produces carbon monoxide, hydrogen chloride and other toxic gases when burned



Run off water from firefighting may have corrosive effects Section V—Reactivity Data Stability Unstable Conditions to Avoid N/A Stable N/A Incompatibility (Materials to Avoid) N/A Hazardous Decomposition or Byproducts Emits Co, Co 2, hydrogen chloride, organotins and various hydrocarbons with combustion May Occur Conditions to Avoid N/A Polymerization N/A Will Not Occur Section VI—Health Hazard Data Inhalation? Route(s) of Entry N/A Ingestion? Avoid inhalation of combustion products Health Hazards (Acute and Chronic) NTP? IARC Monographs? OSHA Regulated? Carcinogenicity N/A Combustion products may cause eye, nose and throat irritation Signs and Symptoms of Exposure Medical Conditions Generally Aggravated by Exposure N/A Emergency and First Aid Procedures Remove individual from fire area. Call physician Section VII—Precautions for Safe Handling and Use Steps to Be Taken in Case Material Is Released or Spilled N/A Waste Disposal Method Sanitary landfill Precautions to Be Taken in Handling and Storing Water Sprinkler warehouse recommended Other Precautions None Section VIII—Control Measures Respiratory Protection (Specify Type) **N/A** Ventilation Local Exhaust N/A Special N/A Other N/A Mechanical (General) N/A Protective Gloves None Eye Protection None Other Protective Clothing or Equipment None



Work/Hygienic Practices None